

Micro Router, Mighty Connectivity A tiny dual-cellular router that can fit anywhere

# Unbreakable cellular connectivity in the smallest footprint possible



Dual-cellular modems





peplink

SpeedFusion technology for high reliability connections

## Reliable routing that fits virtually anywhere

peplink

Smaller than a stack of 3 decks of cards, the BR2 Micro fits where no others can.

Ethernet or USB-C data connections



# Instant configurability

Built-in eSIM enables zero-touch provisioning, configuration and management.





eSL

Remote device management with Peplink InControl and InTouch eliminates the need for pre-staging configurations.

C 2 2 🔍



## Ruggedized metal enclosure with flexible, low power options

#### Operates across wide temperature ranges -40°F - 149°F / -40°C - 65°C

GN I/P

### Fanless design

## Low power consumption with a USB-C power input option

Cost-effective and scalable for mass deployment

\*Pricing applies to US region only, other regions may vary.

# **BR2 Micro**



1x GE WAN/LAN port 1





#### **Specifications**

WAN Interface	1x 10/100/1000M Ethernet <sup>1</sup> 2x Embedded Cellular Modems	Antenna Connectors	4x MMCX Cellular Antenna Connectors 1x MMCX GPS Antenna Connector
LAN Interface	1x 10/100/1000M Ethernet <sup>1</sup> 1x USB-C <sup>2</sup>	Power Input	AC Adapter: AC Input 100V–240V / DC Output 12V Power Port: 10V – 30V DC USB-C Port: 9V DC
SpeedFusion Features <sup>2</sup>	Hot Failover, Smoothing, Bandwidth Bonding	Power Consumption	8W (nominal) , 13W (max.)
No.of SpeedFusion VPN Peers	2 / 5 <sup>3</sup>	Dimension	2.99 x 3.25 x 1.69 inches / 76 x 83 x 43 mm
Router Throughput	300Mbps	Weight	0.77 pounds / 350 grams
SpeedFusion VPN Throughput - No Encryption - 256-bit AES	80Mbps 60Mbps	Operating Temperature	-40° – 149°F / -40° – 65°C
		Humidity	15% – 95% (non-condensing)
Recommended Users	1 - 60	Certifications	FCC, CE, RoHS EN 61000 Electromagnetic Compatibility
Cellular Data Rate <sup>4</sup> (Downlink/Uplink)	CAT-4: 150 Mbps / 50 Mbps	Package Content	1x BR2 Micro 1x 12V 2A 4 Pin Power Supply (ACW-632) 1x USB-C to USB-C Cable with Screw Locking (ACW-620) 1x USB-C to USB-A Adapter (ACW-622) 4x M2.5 x 3mm Screws 1 pair of Mounting Brackets
		SIM Option	Nano-SIM (4FF) Peplink eSIM BYO eSIM (2 profiles per modem) RemoteSIM from SIM Injector FusionSIM
		Warranty	1-Year Limited Warranty

<sup>1</sup> WAN port can be configured as LAN port via the Web Admin.
<sup>2</sup> The USB-C LAN interface is equipped with Ethernet to USB Adapter based on the AX88179 chipset, enabling virtual Ethernet connectivity for any device through a USB connection. Please ensure the appropriate drivers are installed.
<sup>3</sup> Requires a PrimeCare subscription, complimentary for the first year.

<sup>4</sup> Theoretical maximum data rates.

Specifications are subject to change without notice.

# **BR2 Micro**



#### **Ordering Information**

Product Code MAX-BR2-MICRO-LTE-US-PRM Embedded Modem(s): 2x CAT-4	Regions^ North America* *US Carrier Certifications: AT&T, T-Mobile, Verizon, FirstNet	<b>LTE Bands</b> B2, B4, B5, B12, B13, B14, B66, B71	<b>3G Bands</b> B2, B5
MAX-BR2-MICRO-LTE-E-PRM Embedded Modem(s): 2x CAT-4	APAC, EMEA	B1, B3, B5, B7, B8, B20, B38, B40, B41	B1, B5, B8

^ Regions are for reference only. For specific location compatibility, please refer to the bands.

#### **Featured Add-ons**

Product Code	Description
PRM-B-1Y / PCP-B-1Y	PrimeCare B / PrimeCare+ B (1-Year)
PRM-B-2Y / PCP-B-2Y	PrimeCare B / PrimeCare+ B (2-Year)
PRM-B-4Y / PCP-B-4Y	PrimeCare B / PrimeCare+ B (4-Year)
ACW-634	10ft / 3m DC Power Cable
ACW-643	Vehicle Cigarette to Molex Power Cable
ACW-791	Peplink 4-Pin Micro-Fit to USB-C Power Cable
BR2-MICRO-ACW-KIT	BR2 Micro Accessory Kit • 4x 3m MMCX to SMA-F Magnetic Cellular Antenna Base (ACW-414) • 1x 5m MMCX Magnetic GPS Antenna (ACW-415)

• 4x Cellular Antenna (ACW-237)